

WEBER



WES 62.5



WES 62.5



WEBER

GENERATING SET MODEL WES 62.5

Output Ratings	Prime
400 V,3 ph,50 Hz,1500 rpm	62.5 Kva
	50 kW
	Power Factor : 0.8

ENGINE / TECHNICAL DATA

Engine Make	Volvo Eicher
Engine Model	EE483TCI
Governing Type	Mechanical
Number of Cylinders	4
Rated BHP	80
Bore and Stroke mm	100 X 105
Displacement ltrs	3.3
Electric System	12 V DC
Compression Ratio	17:01
Injection system	Direct
Cylinder arrangement	Inline
Nature of Aspiration	TCI

STANDARD SPECIFICATIONS

1. Eicher heavy duty high performance industrial type diesel engine
2. ENGINE FILTRATION SYSTEM
 - Cartridge type dry air filter
 - Two cartridge type fuel filters
 - Full flow lube oil filterAll filters have replaceable elements
3. COOLING RADIATOR
Radiator and cooling fan, complete with safety guards, designed to cool the engine at high ambient temperatures (consult your dealer for deration factors)
4. EXHAUST SYSTEM
Heavy duty Industrial Exhaust Silencer

Silencer noise reduction level 15 (dB)
Maximum allowable back pressure 10.0 (kPa)
5. CIRCUIT BREAKER TYPE
ABB 3 pole MCCB, (4 pole is optional)
6. FUEL SYSTEM
On Generating sets upto 700kVA, the baseframe design is incorporated with an integral fuel tank with a capacity of approx. 8 hours running at full load. The tank is supplied complete with fill cap breather, fuel speed and return lines to the engine and drain plug.
7. ALTERNATOR
7.1 INSULATION SYSTEM
 - Insulation : Class H
 - All windings are impregnated in either a triple dip thermosetting liquid, oil and acid resisting polyester varnish or vacuum pressure impregnated with a special polyester resin.
 - Heavy coat of antitracking varnish additional protection against moisture or condensation.
- 7.2 AUTOMATIC VOLTAGE REGULATOR (AVR)
The fully sealed AVR maintains the voltage regulation at $\pm 0.5\%$. Nominal adjustment by means of a trim pot incorporated on the AVR.
- 7.3 MOTOR STARTING
An overload capacity equivalent to 300% of the full load impedance at zero power factor can be sustained for 10 sec., when AREP or PMG option is fitted.
8. MOUNTING ARRANGEMENT
8.1 BASE FRAME
The complete generating set is mounted as a whole on a heavy duty fabricated steel baseframe.
- 8.2 COUPLING
The engine and alternator are directly coupled by means of an SAE flange. The engine flywheel is flexibly coupled to the alternator rotor.
- 8.3 ANTI-VIBRATION MOUNTING PADS
Anti-vibration pads are affixed between the engine / alternator feet and the baseframe thus ensuring complete vibration isolation of the rotating assembly.

ENGINE / TECHNICAL DATA (continued)

Frequency and Engine Speed	50Hz & 1500rpm
	Prime
No. of Valves / Cyl	2
Cooling system	Liquid
Dimensions (L x W x H) mm	1182x802x1108
Dry Weight kg	410
Noise Level dB(A) (Without Canopy)	94 @ 1 mtr
FIP Make	Bosch Inline
Lube oil sump capacity (Ltrs.)	11
BSFC @ 100% load (gms/hp-Hr)	156
BSFC @ 75% load (gms/hp-Hr)	157
Lube Oil Consumption (% of Fuel Cons.)	0.1

Dimension (mm) & Weight (Kg)	Length	Width	Height	Weight
Open	1980	900	1350	1150
Soundproof	2800	1110	1770	1690

ALTERNATOR DATA

Make	Leroy Somer TAL / Stamford
Model	TAL 042H / UCI224E
No. of bearings	1
Insulation Class	H
Total Harmonic Content	on load < 5%
Wires	6 / 12
Ingress Protection	IP23
Excitation System	Shunt / Self Excited
Winding Pitch	2/3(n°6)
AVR Model	R120 / SX460
Overspeed	2250 mn ⁻¹
Voltage Regulation	±1% / ±1.5%
Short Circuit Capacity	-
AREP & PMG Excitation System Available as optional	

STANDARD SPECIFICATIONS

8.4 SAFETY GUARDS

The fan and fan drive along with the battery charging alternator are safety guard protected for personnel protection.

9. FACTORY TESTS

- The generating set is load tested before dispatch.
- All protective devices control functions and site load conditions are simulated. The generator and its systems are checked before dispatch.

10. EQUIPMENT FINISHING

All mild steel components are fully degreased and painted with powder coated paint to ensure maximum scuff resistance and durability.

11. DOCUMENTATIONS

Operation and Maintenance manual and circuit wiring diagrams are accompanied with the generator.

CONTROL PANEL

Make Deep Sea
Model DSE4510

The DSE4510 is an Auto Start Control Module for single genset applications. It includes a backlit LCD display which clearly shows the status of the engine all the times. This module can either be programmed using the front panel or by using the DSE configuration suite PC software.

Metering and Alarm Indications:

- Generator Frequency
- Underspeed, Overspeed
- Generator volts (L-L, L-N)
- Generator Current
- Engine Oil Pressure
- Engine Coolant Temperature
- Fuel Level
- Hours Run Counter
- Battery Volts
- Fail to start/stop
- Emergency Stop
- Failed to reach loading voltage/frequency
- Charge fail
- Loss of magnetic pick-up signal-Optional
- Low DC Voltage
- CAN diagnostics and CAN fail/error



WEBER

Tel: +44 20 8144 2160
Weber Generators Ltd., Office 32,
19-21 Crawford Street, London, W1H 1PJ

Email: info@webergenerators.com
Website: www.webergenerators.com